PENTEK INTELLIDRIVE

Whole home constant pressure system

Homeowners with low water pressure can experience weak showers, unclean dishes, dry lawns and more. Pentair Pentek Intellidrive Constant Pressure System[™] is a variable frequency drive that directs changes in submersible pump motor speed, responding to fluctuations in household demand and includes built-in system protection. This device helps to maintain constant water pressure for private wells.

APPLICATIONS

Residential water systems, landscape irrigation and water transfer use.

SPECIFICATIONS

- Enclosure Dimensions: Width: 9.72" Height: 19" Depth: 6.93"
- Carton Dimensions: Width: 10.4" Height: 22.3" Depth: 9.4"
- Shipping Weight: 22 pounds
- Ambient Temperature Range: -20°C (-4°F) to 50°C (122°F)
- Ambient Humidity Range: 95% non-condensing
- Includes: Variable Frequency Drive
- Transducer: 1/4" thread size, 18 NPT type
- Transducer Cable: 10' length standard

VFD-LINK SPECIFICATIONS

- 900MHz Communication
- 100ft range between Communication Hub device and Gateway. May extend additional 300ft with Cat5e cable
- Includes: Communication Hub, Gateway, Cat5e cable, power adapters, and cord grip.



Start protecting your home today at Pentair.com/Pentek



FEATURES

FEATURES

4 Models for More Installation Opportunities

- 1/2 HP 5 HP Capabilities
- All in the same unit; 2-Wire, 3-Wire & 3-Phase
- Submersible motors
- 3-Phase Above Ground motors
- 1-Phase Input *230V)
- 80 Hz 3-Phase Output option**

Designed to Last

- "Soft Start/Coast to Stop" minimizes mechanical stress.
- Constant pressure helps to eliminate frequent on/off pressure cycling

** Ongoing 80Hz operation may reduce the life of the pump and motor.

ORDERING INFORMATION

GET CONNECTED

Add the VFD-LINK Accessory for Remote Monitoring

- Ease of installation: Simply connect to Pentair Pro App, install two wires to the Pentek Intellidrive[™] Constant Pressure System and plug in the communication hub and gateway. Easy touchpad operation allows for installation, system monitoring and troubleshooting.
- Alerts for common issues: Provides notifications to the homeowner who can turn the drive on and off remotely.
- **System Status:** View system status and drive settings remotely for added troubleshooting.
- Can enhance service experience and opportunities: With your customer's permission, you can receive notifications and alerts. This can create opportunities for you as the dealer to offer additional services based on status information.

MODEL NUMBER	MOTOR TYPE	HP RANGE	MAXIMUM OUTPUT AMPS	INPUT VOLTAGE	ENCLOSURE TYPE	
PID10	2-WIRE 1-PHASE		9.5A			
	PID10	3-WIRE 1-PHASE	– 0.5 – 1 HP	7.5A		
	3-PHASE	-	5A	1001/ 0051/		
PID20	2-WIRE 1-PHASE	0.5 – 1.5 HP	11A			
	3-WIRE 1-PHASE		13.5A			
	3-PHASE	0.5 – 2 HP	8.5A			
PID30	2-WIRE 1-PHASE	0.5 – 1.5 HP	11A	190V - 265V	NEMA 3R outdoor	
	3-WIRE 1-PHASE	0.5 – 2 HP	13.5A			
	3-PHASE	0.5 – 3 HP	11.5A			
PID50	2-WIRE 1-PHASE	0.5 – 1.5 HP	11A			
	3-WIRE 1-PHASE	0.5 – 2 HP	13.5A			
	3-PHASE	0.5 – 5 HP	18A			

CATALOG NUMBER	DESCRIPTION	ENCLOSURE	WEIGHT
VFD-LINK	Wireless Translator for Pentek Intellidrive	NEMA 1	2

FEATURES

KEYHOLE MOUNT

For fast and easy installation

LCD INFORMATION CENTER Displays installation, status and fault information in easy-to-understand language instead of codes

GROUND DETECTION Message Center shows if there is a grounding problem

MULTIPLE ACCESSORY INPUTS Additional inputs allow use of

multiple drive accessories at the same time

EMI/RFI FILTER Superior noise and interference protection, including AM radio signals

SPACIOUS WIRING AREA Work with ease

PROGRAMMABLE INPUT/OUTPUT RELAYS Provides application flexibility

EASY-ACCESS CONDUIT OPENINGS

Align with appropriate terminals for straight-in accessibility. Fits 1/2", 3/4" or 1-1/4"





ELECTRONIC PRESSURE TRANSDUCER More accurate and reliable than mechanical pressure switch, with piezo resistive technology designed to resist

TEMPERATURE- SENSITIVE INTELLIGENT FAN Operates when needed for quieter operation

SD CARD SLOT

water hammer

For easy software updates when provided by manufacturer


SPRING TERMINALS

For secure connections and easy installation without special tools

REMOVABLE TERMINAL BLOCKS

For easier wiring of motor and power supply – field replaceable

OUTLINE DIMENSIONS



ACCESSORIES

PENTEK INTELLIDRIVE[™] CONSTANT PRESSURE SYSTEM ACCESSORIES

MODEL NO.	DESCRIPTION	
VFD-LINK	Wireless Translator for Intellidrive	
VFD-SGA	Surge arrestor kit, line and load	
VFD-SGA-LN	Surge arrestor kit, line side	
VFD-SGA-LD	Surge arrestor kit, load side	
VFD-ALT	VFD Alternating panel	
VFD-WS	VFD Water sensor with 15' cable	
VFD-SCRN	Filter Kit	

PENTEK INTELLIDRIVE TRANDUCER CABLES

PART NUMBER	DESCRIPTION
VFD-10TCB	Transducer Cable 10FT 3R
VFD-20TCB	Transducer Cable 20FT 3R
VFD-50TCB	Transducer Cable 50FT 3R
VFD-100TCB	Transducer Cable 100FT 3R
VFD-200TCB	Transducer Cable 200FT 3R

PENTEK INTELLIDRIVE REPAIR PARTS

MODEL NO.	ITEM	DESCRIPTION
PID-CON2	2-Pole Connector (Line In)	2-Pole Connector (Line In)
PID-CON3	3-Pole Connector (Line Out)	3-Pole Connector (Line Out)
PID-FAN	Replacement Fan	Replacement Fan
PID-HMI	Replacement Keypad	Replacement Keypad
U17-1561-R	Transducer (PID Control)	0 - 100 psig, 4~20ma, less lead
U17-2000	Transducer (PID Control)	0 - 300 psig, 4-20ma, less lead

Pentair Pentek® Transducer for use with Pentek Intellidrive and Intellidrive XL.



VFD-WS

VFD Water sensor with 15' cable



VFD-ALT VFD Alternating panel



VFD-LINK Wireless Translator for Pentek Intellidrive

ASSEMBLED IN THE USA WITH FOREIGN AND DOMESTIC COMPONENTS

293 Wright Street | Delavan, WI 53115 | United States | 888-782-7483 | F: 800-426-9446 | pentair.com

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.